















2.7~13.5mm Vari-Focal Lens

Triple Codecs

Smart IR™

Warranty

# Summary

This MEGApix® IP camera provides 2.1MP/1080p resolution at real-time 30fps. It includes a 2.7~13.5mm vari-focal lens and simultaneous H.265/H.264/MJPEG codec support, all in an IP66 weather-resistant bullet housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

#### **Features**

- · 2.1MP/1080p 1/2.9" image sensor at real-time 30fps
- · 2.7~13.5mm vari-focal lens
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync.
- Smart DNR™ 3D digital noise reduction
- · True day/night mechanical IR cut filter
- · Digital Wide Dynamic Range (D-WDR)
- · Programmable privacy zones
- · Auto gain control (AGC)
- · Backlight compensation (BLC)
- · Auto white balance (AWB)
- Motion detection
- · Web server built-in
- · PoE class 3 and DC12V
- · Waterproof cabling
- · ONVIF conformant, profile S
- · IP66 environmental-rated dust-tight and water-resistant
- · 5 year warranty



#### Accessories (Optional)




**DWC-BLJUNC** Junction box



DWC-PMR-RU Pole mount

### **Dimensions**

unit: Inch (mm)



# **Specifications**

<u> </u>	
IMAGE	
Image sensor	2.1MP/1080p 1/2.9" CMOS
Total pixels	2001(H) X 1121(V)
Minimum scene illumination	0.16 lux (color)
	0.0 lux (B&W)
LENS	
Focal length	2.7-13.5mm, F1.6
Lens type	Vari-focal lens
Field of view (FoV)	27° ~ 89.6°
IR distance	100ft range
OPERATIONAL	
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter	2X, 3X, 5X, 6X, 7.5X, 10X
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital	3D-DNR
noise reduction	
Wide Dynamic Range (WDR)	D-WDR
Privacy zone	16 programmable privacy masks
Backlight Compensation (BLC)	Yes
Mirror & flip	Yes
Alarm notifications	Notifications via e-mail and FTP server recording
NETWORK	
LAN	RJ45(10/100Base-T)
Video compression type	H.265, H.264, MJPEG
•	H.265: 2.1MP/1080p, 720p(main), CIF(sub)
Resolution	H.264: 2.1MP/1080p, 720p(main), CIF(sub)
	MJPEG: CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for preview and recording
Dituate control	Multi streaming CBR/VBR at H.264, H.265
Bitrate control	(controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4
Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP,
	SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF
Security	HTTPS(SSL), IP filtering, 802.1x, digest authentication(ID/PW)
ONVIF conformance	Yes
OTT THE COMPONITION OF	OS: Windows*, Mac* OS, Linux*
Web viewer	
viewei	Browser: Internet Explorer*, Google Chrome*, Mozilla Firefox*, Safari*
Video management software	DW Spectrum* IPVMS
ENVIRONMENTAL	DW Spectrum in Vivis
	-4°F ~ 122°F (-20°C ~ 50°C)
Operating temperature	
Operating humidity	10-90% (non-condensing)
IP rating	IP66 certified
Other certifications	CE, FCC, RoHS
ELECTRICAL	DO 101/ D. E. (IEEE 000 = 1.5)
Power requirement	DC 12V, PoE (IEEE 802.3af Class 3). (Adapter not included)
Power consumption	DC12V: max 5.2W PoE: max 7.0W
MECHANICAL	1 32ax 7.0 11
Material	Aluminum bullet housing
Dimensions	9.92" x 3.81" (252 x 96.7 mm)
Weight	1.65 lbs (0.75kg)
AACIGIII	
Warranty	5 year warranty









