

















Star-Light Plus™

4.0mm Fixed Lens

True WDF

lecs Warrar

Summary

This MEGApix® IP camera provides 2.1MP/1080p resolution at real-time 30fps. It includes a 4.0mm fixed lens, simultaneous H.265/H.264/MJPEG codec support and Star-Light Plus™ color in near-total darkness technology for quality video in any lighting condition, all in an IP67 dust-tight and waterproof bullet housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.


Features

- · 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus[™] color in near-total darkness technology
- · 4.0mm fixed lens
- · True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Smart DNR™ 3D digital noise reduction
- · True day/night mechanical IR cut filter
- · Programmable privacy zones
- · Auto gain control (AGC)
- · Auto white balance (AWB)
- · Motion detection
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- · Web server built-in
- PoE class 2 and DC12V
- · ONVIF conformant, profile S
- · IP67 dust-tight and water-proof to 3 feet
- 5 year warranty



Dimensions

unit: Inch (mm)



Specifications

IMAGE	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.09 lux (color)
LENIC	0.0 lux (B/W)
LENS	4.0 50.0
Focal length	4.0mm, F2.6
Lens type	Fixed lens
Field of view (FoV)	86°
IR distance	100ft range
OPERATIONAL	A. t
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter Auto gain control	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10 Auto
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital	
noise reduction	3D-DNR
Wide Dynamic Range (WDR)	True WDR
Wide Dynamic Range (WDR) dB	120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications,
	FTP and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (SSL), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
	OS: Windows*, Mac* OS, Linux*
Web viewer	Browser: Internet Explorer*, Google Chrome*, Mozilla Firefox*, Safari*
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% (non-condensing)
IP rating	IP67-rated
Other certifications	
Other certifications	CE, FCC, RoHS
ELECTRICAL	CE, FCC, RoHS
	CE, FCC, RoHS DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included)
ELECTRICAL	DC 12V, PoE (IEEE 802.3af Class 2).
ELECTRICAL Power requirement	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included) DC12V: max 4.5W
ELECTRICAL Power requirement Power consumption	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included) DC12V: max 4.5W
Power requirement Power consumption MECHANICAL	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included) DC12V: max 4.5W PoE: max 6.0W
ELECTRICAL Power requirement Power consumption MECHANICAL Material	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included) DC12V: max 4.5W PoE: max 6.0W







