

## 5MP bullet IP camera DWC-MB75Wi4T



## Summary

This MEGApix<sup>®</sup> IP camera is TAA / NDAA compliant and provides 5MP resolution at real-time 30fps. It includes a 4.0mm fixed lens, simultaneous H.265/H.264/MJPEG codec support with dual-stream and Star-Light Plus<sup>™</sup> color in near-total darkness technology for quality video in any lighting condition, all in an IP67 dust-tight and waterproof bullet housing. All MEGApix<sup>®</sup> cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

## Features

- 5MP 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 4.0mm fixed lens
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Smart DNR™ 3D digital noise reduction
- $\cdot$  True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Micro SD/SDHC/SDXC class 10 card slot (card not included)

: sales@dwcc.tv

- Web server built-in
- PoE class 3 and DC12V
- TAA / NDAA compliant


: 866.446.3595

- ONVIF conformant, profile S
- $\cdot$  IP67 dust-tight and waterproof to 3 feet
- 5 year warranty



 $(\square)$ 

Dimensions unit: Inch (mm)



## Specifications

IMAGE	
Image sensor	5MP 1/2.8" CMOS
Total pixels	2560 (H) x 1440 (V)
	0.16 lux (color)
Minimum scene illumination	0.0 lux (B/W)
LENS	
Focal length	4.0mm, F2.0
Lens type	Fixed lens
Field of view (FoV)	82.3°
IR distance	100ft range
OPERATIONAL	loonthange
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10 Auto
Auto gain control	
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital noise reduction	3D-DNR
Wide Dynamic Range (WDR)	True WDR
Wide Dynamic Range (WDR) dB	120dB
Privacy zone	
	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications,
Memory slot	FTP and SD card recording Micro SD / SDHC / SDXC (card not included)
	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2592x1944, 2304x1296, 2,1MP/1080p.
	H.265: 2592x1944, 2304x1296, 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2592x1944, 2304x1296, 2.1MP/1080p,
	H.264: 2592x1944, 2304x1296, 2.1MP/1080p,
	720p, VGA, D1, CIF
	MJPEG: 2.1MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for
	preview and recording Multi streaming CBR/VBR at H.264, H.265
Bitrate control	(controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
IF	
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, F1
	SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
	HTTPS (TLS), IP filtering, 802.1x,
Security	digest authentication (ID/PW)
ONVIF conformance	Yes
City in comornance	OS: Windows®, Mac® OS, Linux®
Web viewer	
web viewer	Browser: Internet Explorer <sup>®</sup> , Google Chrome <sup>®</sup> ,
	Mozilla Firefox*, Safari*
Video management software	DW Spectrum <sup>®</sup> IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% (non-condensing)
IP rating	IP67-rated
Other certifications	CE, FCC, RoHS
ELECTRICAL	
	DC 12V, PoE (IEEE 802.3af Class 3).
Power requirement	(Adapter not included)
	DC12V: max 6.5W
Power consumption	PoE: max 8.3W
·	
MECHANICAL	Aluminum bullet bousing
MECHANICAL Material	Aluminum bullet housing
MECHANICAL Material Dimensions	6.41" x 2.65" (163 x 67.5 mm)
MECHANICAL Material	



REV: 11/20

: www.digital-watchdog.com