



## Flush Mount IP Camera

**6525-B: Black / 6525-O: Oil Rubbed Bronze / 6525-W: White**

Channel Vision's Flush Mount IP Camera features superior image quality with a 2 megapixel CMOS sensor and the ability to capture high definition 1080p images. The 6525 is designed for discrete placement in a double gang box, and comes in your choice of a black, oil rubbed bronze or white faceplate. This camera also contains 36 Camera Central Management Software (CMS) to allow users to view all of their cameras in the same window from anywhere in the world.



### FEATURES

**Power over Ethernet**

**High Definition 1080p at 30 FPS**

**Digital Wide Dynamic Range**

**Micro SD card recording**

**Vandal Proof Dome**

**IP66 Weatherproof Rating**

### SPECIFICATIONS\*

\*Specifications subject to change.

#### Hardware

**CPU:** Arm 9, 32 bit RISC

**RAM:** 128MB

**Flash:** 16MB

**Image Sensor:** 1/2.7" CMOS Sensor

**Sensitivity:** Color: 0.1 Lux (AGC On)

**Lens Type:** 2.8 mm

**Power Over Ethernet:** Yes, 48V power Consumption

**Operating Temp:** 14 °F - 113 °F (-10 °C - 45 °C)

**Dimensions:** 4.75 x 4.75 plate and 3" depth

**Field of View:** 111.10 ° (H) x 65.10 ° (V)

#### Network

**Ethernet:** 10/100 Base-T

**Network Protocol:** HTTP, HTTPS, SNMP, QoS/DSCP, Access

List, IEEE, 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, BONJOUR, ONVIF

#### Live Viewing

**OS:** Windows XP, 7, 8 or Macintosh Version 10.6 or newer

**SBrowser:** Microsoft IE 6.0 or newer, Safari, Firefox & Chrome

**Suggested Hardware:** Intel Dual Core 1.66G, RAM: 1024MB, Graphic card: 128 MB (Windows)

#### System

**Video Resolution:** 1920x1080 (Max), 1280x720, 640x480, 320x240, 126x144

**Video Adjustments:** Brightness, Contrast Hue, Saturation, Sharpness, AGC, Shutter Speed adjustable, Sense-up, D-WDR, Flip, Mirror, Noise reduction, DNR

